

Hearing Protective Device Test Report Number Q7025A Revision 1

Shanghai Langfeng Industrial Co., Ltd.  
Room 910, Building 6, Luxiang road 111,  
Shanghai, China

Date of Report: 10/11/21

Date of testing: 9/8/21-10/6/21

Date of Sample Receipt: 9/3/21



Technician: Eileen Kline

Attenuation measurements have been performed according to the American National Standards Institute (ANSI) Specifications, ANSI S3.19-1974, using the experimenter-fit protocol, on the Shanghai Langfeng Industrial Co., Ltd. EM-5002 Noise Defender Pro muff-type hearing protector (test ID Q7025A). The specified threshold measurement data were obtained using ten normally-hearing listeners, six male and four female. These listeners were selected from a standby group of about 35 volunteers who regularly serve as listeners for measurements of this kind.

The measurements were made in a room designed for this purpose. All acoustic characteristics of the room meet the requirements outlined in ANSI S3.19-1974. The ambient noise levels in this room are below the limits specified in ANSI S3.19-1974, and open ear thresholds are used on a continuing basis to monitor the background noise levels. An automatic recording attenuator was used to record both open and occluded ear thresholds.

Each of ten subjects was tested three times at each of nine test frequencies. The attached Tables show grand mean attenuation values in decibels (dB) for each test signal along with group attenuation values. Standard deviations (S.D.) for the 30 different attenuation determinations for each test signal are also given. The results presented in this report pertain to the samples tested only.

Michael & Associates is accredited by the National Institute of Standards and Technology (NIST) National Laboratory Accreditation Program (NVLAP) for tests performed according to ANSI S3.19-1974, ANSI S12.6-2016, AS/NZ S1270:2002 and EN352 parts 1-10. These accreditation criteria encompass the requirements of international standard ISO 17025. This report may only be reproduced or transmitted electronically in its' entirety. This report shall not be used to claim product certification, approval or endorsement by NIST, NVLAP or by any agency of the U.S. Government. All measurement equipment are calibrated with instrumentation traceable to the NIST. Accreditation documentation can be viewed at [www.michaelassociates.com/data/documents/NVLAP-2025.pdf](http://www.michaelassociates.com/data/documents/NVLAP-2025.pdf).

*Use these laboratory-derived attenuation data for comparison purposes only. The amount of protection afforded in field use is often significantly lower depending on how the protectors are fitted and worn.*

A handwritten signature in black ink, appearing to read 'Calvin Michael', is written over a horizontal line.

Calvin Michael, MSS, Director of Operations

8/12/25

Date

**Individual and Summary Attenuation Data for  
Hearing Protective Devices**

Test Method: ANSI S3.19-1974

Manufacturer: Shanghai Langfeng Industrial Co., Ltd

Model: EM-5002 Noise Defender Pro

Position: Over-the-head

Date: 10/11/21

Test ID: Q7025A

| SUBJECT   | Frequency in Hz |      |      |      |      |      |      |      |      |
|-----------|-----------------|------|------|------|------|------|------|------|------|
|           | 125             | 250  | 500  | 1000 | 2000 | 3150 | 4000 | 6300 | 8000 |
| 1         | 16              | 24   | 35   | 43   | 34   | 36   | 36   | 35   | 39   |
|           | 16              | 24   | 34   | 40   | 36   | 34   | 36   | 35   | 41   |
|           | 15              | 24   | 35   | 43   | 33   | 33   | 37   | 36   | 40   |
| 2         | 18              | 26   | 33   | 40   | 34   | 35   | 37   | 38   | 34   |
|           | 17              | 26   | 32   | 43   | 35   | 33   | 37   | 36   | 38   |
|           | 18              | 25   | 34   | 42   | 35   | 31   | 37   | 37   | 36   |
| 3         | 16              | 22   | 27   | 35   | 32   | 36   | 36   | 37   | 33   |
|           | 14              | 21   | 29   | 37   | 35   | 35   | 35   | 37   | 34   |
|           | 15              | 20   | 27   | 36   | 34   | 37   | 36   | 39   | 33   |
| 4         | 20              | 27   | 35   | 42   | 36   | 41   | 42   | 39   | 34   |
|           | 19              | 27   | 33   | 43   | 36   | 40   | 39   | 40   | 34   |
|           | 17              | 27   | 35   | 43   | 36   | 40   | 39   | 39   | 33   |
| 5         | 15              | 23   | 34   | 40   | 38   | 34   | 39   | 34   | 35   |
|           | 15              | 22   | 32   | 38   | 38   | 35   | 40   | 36   | 36   |
|           | 13              | 23   | 32   | 38   | 37   | 35   | 36   | 36   | 34   |
| 6         | 21              | 26   | 35   | 40   | 39   | 37   | 44   | 40   | 34   |
|           | 19              | 27   | 38   | 44   | 38   | 37   | 48   | 40   | 36   |
|           | 18              | 25   | 39   | 43   | 39   | 35   | 45   | 41   | 37   |
| 7         | 15              | 22   | 33   | 34   | 35   | 38   | 40   | 36   | 36   |
|           | 16              | 22   | 32   | 35   | 32   | 38   | 41   | 37   | 37   |
|           | 18              | 25   | 33   | 34   | 34   | 37   | 44   | 38   | 38   |
| 8         | 17              | 24   | 34   | 36   | 32   | 34   | 40   | 33   | 31   |
|           | 19              | 22   | 34   | 37   | 32   | 33   | 38   | 30   | 32   |
|           | 22              | 23   | 34   | 37   | 32   | 36   | 39   | 33   | 31   |
| 9         | 20              | 24   | 31   | 40   | 39   | 33   | 35   | 37   | 33   |
|           | 18              | 21   | 28   | 32   | 38   | 32   | 34   | 35   | 32   |
|           | 18              | 22   | 30   | 41   | 39   | 35   | 35   | 35   | 32   |
| 10        | 20              | 21   | 27   | 37   | 32   | 29   | 36   | 29   | 30   |
|           | 18              | 19   | 29   | 38   | 39   | 28   | 35   | 30   | 32   |
|           | 17              | 18   | 27   | 42   | 38   | 32   | 35   | 34   | 31   |
| MEANS     | 17.2            | 23.3 | 32.4 | 39.1 | 35.5 | 34.9 | 38.3 | 36.0 | 34.6 |
| STD. DEV. | 2.2             | 2.4  | 3.2  | 3.3  | 2.5  | 3.0  | 3.4  | 3.0  | 2.9  |

NRR = 26 dB

CSA Class = A

Headband Force = 2.2 lbs

*Use these laboratory-derived data for comparison purposes only. The amount of protection afforded in field use is often significantly lower depending on how the protectors are fitted and worn.*

Manufacturer: Shanghai Langfeng Industrial Co., Ltd  
Model: EM-5002 Noise Defender Pro  
Position: Over-the-head

Date: 10/11/21  
Test ID: Q7025A

Measurements were made according to American National Standards Institute Specifications ANSI S3.19-1974.

Special considerations during test: None

Test Item: Q7025A



These data were obtained through measurements made at the laboratories of Michael & Associates, Inc., State College, PA , USA. Michael & Associates, Inc., is accredited to test to ANSI S3.19-1974, ANSI S12.6-2016, ANSI S12.42-2010, EN352 parts 1-8 and AS/NZ S1270:2002 by the National Institute of Standards and Technology (NIST) National Voluntary Laboratory Accreditation Program (NVLAP).

Calvin Michael, MSS  
Director of Operations

Date

8/12/25