



# L-7296 (BreazeGuard Pro)

## Breathable & Light-weight Safety Shoes

Upper : Yellow Cow Suede Leather

Lining : BactiVoid™ Breathable Sandwich Air Mesh

Insole : Anti-Fatigue Memory Foam Insoles

Outsole : Flexible PU/PU Injection

Toecap : VortiGard™ Steel Toecap

Penetration : VortiGard™ Steel Midsole Plate

Size : EU 37-47#, UK 3-13#, US4-14#

CE EN ISO 20345:2022+A1:2024 S1P FO SR

ASTM E 2149-2020 Approved Anti-bacteria Lining & Insole (Odor Resistant)

Application : Logistics & Warehouse, Express & Delivery, Repair & Maintenance, Factory Workshop, Garage etc



200 JOULE TOECAP



SLIP-RESISTANT



SHOCK ABSORPTION



ANTI-STATIC



ANTI-NAIL MIDSOLE



PETROL AND CHEMICAL RESISTANT




OIL RESISTANT



### VortiGard™ Steel Toecap Protection • EN ISO 20345:2022

Stainless Steel Toecap is heavy duty and corrosion resistant. The impact resistance can reach 200 joules from falling or rolling objects. The compression resistance can reach 15kN.



### VortiGard™ Steel Plate Protection • EN ISO 20345:2022

Steel midsole plate is flexible and corrosion resistant. The penetration resistance can reach 1100 newtons from nail or other sharp objects. The flex resistance can reach to 1 X 10<sup>6</sup> flexion cycles without visible cracking.



### Cow Suede Leather Upper • EN ISO 20345:2022

Cow suede leather is treated with breathable technology to keep feet from dry from long-time standing or walk. The tear strength of upper leather can reach to 120 Newtons.



### Flexible PU/PU Injection Outsole • EN ISO 20345:2022

Manufactured with Germany Fully Automatic Injection Technology. The outsole is made with PU/PU dual density material. The midsole is 40±5 degree hardness PU, which is soft and shock absorption. The outsole is 65±5 degree hardness PU, which is tough and abrasion resistant.

## Sole Bonding Strength Test

- EN ISO 20345:2022 (Between Upper & Sole)
- Average Test Result  $5.8 \pm 5$  (N/mm)



### Upper, Lining & Bonding Strength Test Result

|                                 |                        |
|---------------------------------|------------------------|
| Upper Tear Strength $\geq$      | 120.0 Newtons          |
| Upper Tensile Properties $\geq$ | 15.0 N/mm <sup>2</sup> |
| Lining Tear Strength $\geq$     | 15.0 N/mm              |
| Bonding Strength $\geq$         | 4.0 N/mm               |

| ✓ Protection With Slip Resistant (SR)                                                                                | Result                                                       |
|----------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------|
| Test Requirement : Forward Heel Slip $\geq 0.31$ (ISO 13287:2019)<br>Backward Heel Slip $\geq 0.36$ (ISO 13287:2019) | PASS                                                         |
| Standards : EN ISO20342:2022(5.3.5) , Test floor: Ceramic tile, Lubricant: Sodium lauryl sulphate                    |                                                              |
| ✓ Protection With Anti-Static                                                                                        | Result                                                       |
| Test Requirement : Anti-static 100K $\Omega$ -1000M $\Omega$ , Test Voltage: 100 $\pm 2$ V DC, Test Period: 1 Minute | PASS                                                         |
| Standards : EN ISO 20345:2022 Dry Humidity (30 $\pm 5$ ) & Wet Humidity (85 $\pm 5$ )                                |                                                              |
| ✓ Protection Resistant to Fuel Oil                                                                                   | Result                                                       |
| Test Requirement : Change in Volume and Change in Hardness (Outsole) is No More Than +12%(*)                         | PASS                                                         |
| Standards : EN ISO 20345:2022                                                                                        |                                                              |
| SAFETOE Standard Package Instruction (Average 42# for Reference)                                                     |                                                              |
| Shoes Weight : 1.1-1.2 KGS /Pair                                                                                     | Carton Weight : 12-13 KGS /Carton                            |
| 1 Pair / Color Box , Dimensions : 32 $\times$ 21 $\times$ 12CM                                                       | 10 Pair / Carton , Dimensions : 62 $\times$ 43 $\times$ 33CM |



### User Instructions:

- 1.) RECOMMENDED TO USE : Logistics & Warehouse, Express & Delivery, Repair & Maintenance, Factory Workshop, Garage etc.
- 2.) LIMITATION TO USE: It is very important that footwear selected must be suitable for the right workplaces. The protection against risks or hazards which are not mentioned in this document is not warranted.
- 3.) FITTING & SIZE: All footwear are marked with standard size on tongue label. Some are with different size comparison, such as EU size, UK size, US size etc. Please wear footwear in a suitable size.

Footwear which are too loose or too tight may not provide optimum level of protection.

- 4.) STORAGE: Keep the footwear in its original packaging, under ordinary temperature, non-humidity conditions and in clean, covered and ventilated premises.
- 5.) CLEANING: Clean footwear regularly by high quality cleaning treatments recommended as suitable for the purpose. Don't use caustic or corrosive cleaning agents.